

Demco

Pro Series

150 & 200 Gallon ATV Sprayer



Features:

- 150 or 200 gallon polyethylene elliptical tank features jet agitation, sump, molded sight gauge and fillwell with a no-splash fillwell cover.
- Trailer frame features height adjustment of up to 18" ground clearance, walking tandem axles with 22 x 11 x 8 pneumatic tires, or single axle with 24x12 turf tires, adjustable wheel spacing of 44" minimum to 90" maximum centers.
- 2" ball coupler hitch.
- Walking tandems feature "lock out" for rigid axle spraying.
- A 2 ½ gallon clean water tank is mounted for added safety.
- PTO driven roller pump: Hypro® cast iron 6 roller pump (C6500D) delivers a maximum of 9.7 GPM at 540 RPM (open flow).
- Hypro® engine driven centrifugal pump: Straight centrifugal pump. Pump delivers 94 GPM at 30 PSI. Maximum pressure is 70 PSI.
- Demco's 21', 28', 30' and 40' Truss-T booms feature horizontal and vertical break-away hinges and ½" rubber hose with no-drip diaphragm check nozzles spaced at 20". 8' transport width.
- 45' Truss Boom features horizontal and vertical break-away hinges and auto level ride, ¾" rubber hose with diaphragm check nozzles spaced at 20". 8' 7" transport width.

Dealer imprint area here.

Demco

P.O. Box 189 • Boyden, Iowa 51234 - 0189
Phone: 1-800-543-3626 • Fax: 1-800-845-6420
View all our products on the web at: www.demco-products.com

Doing Our Best to Provide You the Best